

STANDARD UNE/EN 14411:2016

DRY PRESSED CERAMIC TILES WITH WATER ABSORPTION HIGHER THAN 10%
Wall Tile

Reference: **ERA SANDALWOOD, SKY BLUE, NAVY (DUCTILE)**
ERA BURGUNDY, CHARCOAL (DUCTILE)

Format: ALL SIZES

Thickness: 6 mm

| Standard | Features | Required Value | Value |
|---------------------|---|---|-------------------------------|
| Normativas | Características | Valores Requeridos | Valor |
| EN-ISO 10545 / 3 | Water absorption / Absorción de agua | Group BIII / E > 10 % | E > 10 % |
| EN-ISO 10545 / 4 | Breaking strength / Resistencia a rotura | > 200 N | > 400 N |
| EN-ISO 10545 / 4 | Bending strength / Resistencia a la flexión | > 12 N/mm ² | > 12 N/mm ² |
| EN-ISO 10545 / 9 | Resistance to thermal shock / Resistencia al choque térmico. | Required / Exigida | Complies with / Cumple |
| EN-ISO 10545 / 11 | Crazing resistance / Resistencia al cuarteo | Required / Exigida | Complies with / Cumple |
| EN-ISO 10545 / 13 | Chemical resistance: acids and alkalis / Resistencia química: ácidos y álcalis | Indicated by the manufacturer / Indicado por el fabricante | GLA Complies with / Cumple |
| EN-ISO 10545 / 13 | Chemical resistance: domestic cleaning products and swimming pool salts / Resistencia química: productos de limpieza doméstica y sales para piscina | Min. GB | GA |
| EN-ISO 10545 / 14 | Stain resistance / Resistencia a las manchas | Min. Clase 3 | Clase 5 |
| EN-ISO 10545 / 2 | Surface quality / Calidad de la superficie | Min. 95% of tiles without defect / Min. 95% de los azulejos sin defecto | Guaranteed / Garantizado |
| UNE EN 13501-1:2002 | Fire Reaction Test / Test reacción al fuego | | A1 / A1FL |
| VOC | Do not release volatile elements / No desprende elementos volátiles | | |

QUALITY DEPARTMENT LIVING CERAMICS

STANDARD INTERNATIONAL ISO 9001
QUALITY MANAGEMENT INTERNATIONAL STANDARD OBTAINED IN 2015.



GREEN BUILDING COUNCIL MEMBERSHIP



T: +34 964 914 181 · F: +34 964 914 250

www.livingceramics.com · info@livingceramics.com